




"LE1" EAVE TRIM



"GU1" GUTTER




"GB1" GUTTER BARS




"GU1EC(R&L)" END CAPS


"GU1ECR" ~ AS SHOWN
"GU1ECL" ~ OPP. HAND



"DS1" DOWNSPOUTS



EAVE w/ TRIM



FOR TYPICAL PIECE MARKS
SEE DETAIL SHOWN ABOVE.

EAVE w/ TRIM & GUTTER

NOTES:

1. GUTTER TO BE CAULKED & LAPPED 4" MIN. AND POP RIVETED TOGETHER USING (8) 1/8" Ø POP RIVETS.
2. FIELD LOCATE AND MARK DOWNSPOUT LOCATION IN BOTTOM OF GUTTER. DRAW LINE FROM CORNER TO CORNER AND CUT ALONG LINE. BEND TABS DOWN AND POP RIVET INSIDE DOWNSPOUT.
3. USE THE CHART TO THE LEFT FOR DIMENSION VALUES FOR YOUR PARTICULAR ROOF PITCH.
4. GUTTER SIZE AND GUTTER BAR SPACING MUST BE ADJUSTED TO SUIT LOCAL WEATHER PECULIARITIES AND/OR TO ACCOMMODATE LONG ROOF SLOPES.

PITCH	"A" DIM.	"B" DIM.	"C" DIM.	"D" DIM.
1:12	95°	115°	85°	6 5/16
2:12	100°	120°	80°	6 3/4
3:12	104°	124°	76°	7 1/8
4:12	109°	129°	71°	7 9/16
5:12	113°	133°	67°	7 15/16



BOX 515 RAILROAD STREET
SANDY LAKE, PENNSYLVANIA 16145-0515
PHONE: 800-245-0396 • FAX: 724-376-3864

2.67" x 1/2" CORRUGATED STANDARD DETAILS

DRAWN BY:

D. JUREY

DATE:

6/10/25

REVISED BY:

DATE:

DRAWING NO.

2.67"x1/2"-5

EAVE DETAILS